

Product Data Sheet

Tile Leveling System

Pre-mixed Polymer Modified Slurry Coating

DESCRIPTION

SEA STAR SEALING SLURRY is a high quality material designed to protect concrete, plasters & building structures from water absorption, moisture & weather effects.

APPLICATION AREAS

- Bathrooms & Toilets
- Water Tanks
- Swimming Pools
- Basement Walls & Foundations
- Balconies
- Rooftops
- Underground Parking Lots
- Other Wet Areas

SURFACE PREPARATION

- Clean the surface and remove any dust, unsound or contaminated material, oil, paint, grease, and corrosion etc.
- Wet the surface slightly with the water.

MIXING INSTRUCTION

Pour one full bag of 1kg sealing slurry into the 600-700ml water (this quantity may vary according to climate conditions) to obtain a solution like paint which can be easily coated with a brush/ roller /

APPLICATION INSTRUCTION

Apply the solution on wet surface with the use of brush / roller / notched trowel in double coat (vertically & horizontally), apply the second coat after the first coat becomes dry.

Once the both coats are applied, let the surface becomes dry completely.

Protect the coated surface from direct sunlight and cover it with plastic sheets for 2 -3 days, afterwards remove the sheets and enjoy the water proof surface.

COVERAGE

SEA STAR SEALING SLURRY covers approx. 25 to 30 Sqft. surface with two coat application.

