

# **Product Data Sheet**

# **Tile Grout Unsanded**

# Fine, Water Resistant, Polymer **Modified, Cement Based Non Shrink Grout. Suitable For Grouting All Types** Of Tiles, Swimming Pool Tiles, **Decorative Stones & Marbles.**



#### **DESCRIPTION**

SEA STAR TILE GROUT (UNSANDED) is a fine, colored powder which, when mixed with water gives a smooth, easily applied creamy paste for clean grouting of tiles. It sets a decorative water resistant finish.

SEA STAR TILE GROUT (UNSANDED) is resistant to cracking in joint upto 3-5mm wide in the hardened state.

#### **COVERAGE**

Grout coverage vary with the tile size and joint width.

#### MIXING INSTRUCTIONS

- Mix SEA STAR GROUT (Unsanded) with clean water at the rate of 3:1 by volume (this ratio may vary according to climate conditions)
- Leave to stand for 10 minutes then stir.
- Don't add excessive water in the mixture, this weakens the grout and makes it much more porous.
- Grout should have consistency of tooth paste when mixed.

#### **APPLICATION INSTRUCTIONS**

- The SEA STAR GROUT (Unsanded) should apply with a smooth face grout float into the joints and press it firmly to ensure that the joints are fill completely.
- Remove surplus grout with a damp sponge.
- When grouting is completed, clean tiles with dry cloth.

### **WATCH POINTS**

Grouting should not start before the tile adhesive has dried out completely.

### **COMPOSITION, PROPERTIES, APPEARANCE**

SEA STAR TILE GROUT (UNSANDED) is a blend of cement, hydrophobic polymer contents, cement fillers, additives and metal oxide color pigments to make it in a variety of colors.

# **PACKAGING**

Available in 1kg bucket, 2kg & 5kg bags.

## SHELF LIFE AND STORAGE

Store out of direct sunlight and protect from water.



