

Product Data Sheet

Multifix – STA 300

General purpose, cement based high quality component, thin or thick bed wall and floor tile adhesive for interiors only

DESCRIPTION

MULTIFIX – STA300 is a cement based general purpose tile adhesive for thin or thick bed fixing of small format tiles (600x600mm) in interior situations. MULTIFIX – STA300 is suitable for fixing materials such as ceramic tiles, porcelain tiles, Marble and Stones.

SUITABLE SUBSTRATE

- CONCRETE
- CEMENT SAND SCREED
- PLASTER

TYPICAL PROPERTIES*

Colors : Off white and Grey
Density : 1.1kg/m³
Yield : A 20kg bag mixed with 5 liters of water yields 15.5 liters of mixed adhesive.
Toxicity : MULTIFIX – STA300 is non-toxic and can be safely used in conjunction with potable water.

COVERAGE

Thin-bed fixing : 3 – 4kg/m² at 3mm thickness (Smooth surface using notched trowel)
Solid-bed fixing : 6 – 8kg/m² at 6mm thickness

APPLICATIONS PROCEDURE

The surface to be tiled should be sound, dimensionally stable, clean and free from dusty or friable materials, paint, grease, oil etc.

APPLICATION INSTRUCTIONS

- Apply MULTIFIX–STA300 to a depth of 3-6mm on working area of not more than 1m². (See Note 1)
- In wet conditions and for floor tiles and for all other vertical applications, the adhesive bed should be combed horizontally with a notched trowel to remove excess.
- Fix dry tiles by pressing into place with slight twisting motion (See Note 2)
- Ensure that at least 90% of each tile is in contact with adhesive.
- Clean off surplus adhesive from the face of the tile with a damp cloth. Similarly, joints must be raked out in readiness for grouting.
- Leave for a minimum of 24 hours before grouting.



Product Data Sheet

Multifix – STA 300

MIXING INSTRUCTIONS

- Mix MULTIFIX – STA300 in clean water at the rate of 3:1 by volume (approx. 5 liters water in a 20kg bag)
- Leave to stand for 5 minutes then stir. Don't add further water.

NOTE

- Solid-bed fixing is recommended for wet conditions and for ceramic, Terrazzo and Marble flooring tiles and vertical applications including decorative Stones. But unlike the application of ordinary tiles, apply to the stone as well.
- Fix tiles (which should be dry) by pressing into place. Beginning at the bottom in the case of wall tiles and at center markings in the case of floor tiles.

WATCH POINTS

- MULTIFIX – STA300 should not be used on painted or metal surfaces.
- The use of chilled water while mixing, will extend open wet time in high ambient temperatures.
- Do not use in damp conditions & temperature below 5 degree.

WORKABILITY

Working time of MULTIFIX – STA300 is about 20 minutes at 25°C, after 20 minutes standing time and tiles must be fixed in position before drying out occurs. For this reason, it is essential to work with in a comparatively small area at a time.

COMPOSITION, PROPERTIES, APPEARANCE

MULTIFIX – STA300 is a blend of Portland cement and graded Sand, reinforced with additive content, with thin / thick bed performance.

COLOURS

MULTIFIX – STA300 is available in Grey & White Colours.

PACKAGING

MULTIFIX – STA300 is available in 20kg bags.

STORAGE

Store out of direct sunlight and protect from water.

PRECAUTIONS AND SAFETY MEASURES

This product contains Portland cement which is slightly alkaline when wet. For people with sensitive skin, continuous use may cause irritation. Gloves or a suitable barrier cream should be used. As a general Code of safety practice all chemical products should be treated with care, kept away from children and animals, especially protect eyes and skin. In emergency seek medical advice.

*** Properties listed are only for guidance and are not a guarantee of performance.**

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and competence of any labour involved in the application are beyond our control.